



SATA III M.2 Solid State Drive
M.2 SSD 800S

Transcend's SATA III 6Gb/s M.2 SSD 800S boasts ultra compact dimensions to address the high performance needs and strict size limitations of small form factor devices, best suited for Ultrabooks and thin, light notebooks. Featuring a powerful controller, exceptional transfer speeds, and MLC NAND flash memory, the M.2 SSD 800S easily handles everyday computing tasks as well as demanding multimedia applications, delivering steadfast reliability.




Perfect for your Ultrabook

Measured at just 80mm in length, the M.2 SSD 800S makes for an easy upgrade to your computer, taking up little space while giving it a much needed energy boost.



Superior transfer speeds

Transcend's M.2 SSD 800S reaches incredible read and write speeds of up to 530MB/s and 460MB/s. When used as a cache, the M.2 SSD 800S provides 1.5 times faster boot time than conventional hard drives.



Store more in less space

The M.2 form factor enables expansion and integration of functions onto a single form factor module solution. M.2 SSDs include a smaller form factor but with larger capacities than that of mSATA and half-slim SSDs.



SATA III M.2 Solid State Drive

M.2 SSD 800S

Features

- Space-saving M.2 Type 2280 form factor
- Up to 512GB storage capacity
- Up to 530 MB/s read; 460 MB/s write
- MLC NAND flash memory and DDR3 DRAM cache
- Supports DevSleep ultra low power state, S.M.A.R.T., TRIM, and NCQ commands



SSD Scope Software

Transcend SSD Scope is advanced, user-friendly software that makes it easy to ensure your Transcend SSD remains healthy, and continues to run fast and error-free by determining the condition and optimizing the performance of your drive.

Specifications

Appearance

Dimensions	80.0 mm x 22.0 mm x 3.58 mm (3.15" x 0.87" x 0.14")
------------	---

Weight	9 g (0.32 oz)
--------	---------------

Interface

Bus Interface	SATA III 6Gb/s
---------------	----------------

Storage

Flash Type	MLC NAND flash
------------	----------------

Capacity	32 GB/64 GB/128 GB/256 GB/512 GB
----------	----------------------------------

Operating Environment

Operating Temperature	0°C (32°F) ~ 70°C (158°F)
-----------------------	---------------------------

Operating Voltage	3.3V±5%
-------------------	---------

Performance

Sequential Read/Write (CrystalDiskMark)	Read: 530 MB/s
	Write: 460 MB/s

4K Random Read/Write (IOMeter)	Read: 70,000 IOPS
	Write: 75,000 IOPS

Mean Time Between Failures (MTBF)	2,000,000 hour(s)
--------------------------------------	-------------------

Terabytes Written (TBW)	1,480 TB
-------------------------	----------

Drive Writes Per Day (DWPD)	2.5 (3 yrs)
--------------------------------	-------------

Note	Speed may vary due to host hardware, software, usage, and storage capacity.
------	---

Warranty

Certificate	CE/FCC/BSMI/KC/RCM
-------------	--------------------

Warranty	Three-year Limited Warranty
----------	-----------------------------

Ordering Information

32GB	TS32GMTS800S
------	--------------

64GB	TS64GMTS800S
------	--------------

128GB	TS128GMTS800S
-------	---------------

256GB	TS256GMTS800S
-------	---------------

512GB	TS512GMTS800S
-------	---------------

SATA III M.2 SSDs Comparison



SATA III 6Gb/s
M.2 SSD 400S



SATA III 6Gb/s
M.2 SSD 600S



SATA III 6Gb/s
M.2 SSD 800S

Appearance

Dimensions	42.0 mm x 22.0 mm x 3.58 mm (1.65" x 0.87" x 0.14")	60.0 mm x 22.0 mm x 3.58 mm (2.36" x 0.87" x 0.14")	80.0 mm x 22.0 mm x 3.58 mm (3.15" x 0.87" x 0.14")
Weight	5 g (0.18 oz)	7 g (0.25 oz)	9 g (0.32 oz)

Storage

Flash Type	MLC NAND flash		
Capacity	32GB ~ 256GB	32GB ~ 256GB	32GB ~ 512GB

Operating Environment

Operating Temperature	0°C (32°F) ~ 70°C (158°F)		
-----------------------	---------------------------	--	--

Performance

Sequential Read/Write (CrystalDiskMark)	Read: 530 MB/s Write: 400 MB/s	Read: 530 MB/s Write: 400 MB/s	Read: 530 MB/s Write: 460 MB/s
4K Random Read/Write (IOMeter)	Read: 70,000 IOPS Write: 70,000 IOPS	Read: 70,000 IOPS Write: 70,000 IOPS	Read: 70,000 IOPS Write: 75,000 IOPS
Mean Time Between Failures (MTBF)	2,000,000 hour(s)		
Terabytes Written (TBW)	740 TB	740 TB	1,480 TB
Drive Writes Per Day (DWPD)	2.5 (3 yrs)		

Warranty

Warranty	Three-year Limited Warranty		
----------	-----------------------------	--	--

Technology

TRIM & NCQ Command	✓	✓	✓
S.M.A.R.T.	✓	✓	✓
DDR3 DRAM Cache	✓	✓	✓
Advanced Garbage Collection	✓	✓	✓
DevSleep Mode	✓	✓	✓
RAID Engine	-	-	-
LDPC Coding	-	-	-

*Speed may vary due to host hardware, software, usage, and storage capacity.