



Card Readers RDF2

Transcend's CFast 2.0 RDF2 Card Reader is exclusively designed for professional cinematographers who pursue extreme transfer efficiency with CFast memory cards. With the USB 3.1 Gen 1 interface, RDF2 shows the amazing transfer speeds. The professionals can save a significant amount of time transferring high-resolution files and focus on their work instead. RDF2's compact and portable design allows the users to easily carry it around with them from studio to the filming spot without adding any burden.



CFast card reader for professional cinematographers

The RDF2 card reader is designed for professional cinematographers who pursue extreme transfer efficiency. It not only supports the next generation CFast 2.0 specification, but is also backward compatible with CFast 1.1 and CFast 1.0 memory cards.



USB Type-A for great device compatibility

The RDF2 card reader is equipped with a micro USB (USB 3.1 Gen 1) port and includes a micro USB to USB Type-A cable to transfer data between your CFast memory cards and your computers.



Higher speeds, higher efficiency

Equipped with the USB 3.1 Gen 1 interface, the RDF2 card reader shows amazing transfer speeds, much faster than what you'd get with USB 2.0! The experts can boost their workflow efficiency by saving a significant amount of time transferring high-resolution files and focus on their professional work instead. In addition, it has an LED indicator to show card insertion and data transfer activity.



Card Readers RDF2

Features

- USB 3.1 Gen 1 interface
- Supports CFast 2.0, CFast 1.1, CFast 1.0 cards
- Compact and portable design
- Designed for high-resolution video, raw image transfers, and post-production processing
- Convenient LED indicator



RecoveRx

RecoveRx is a data recovery software for memory cards, USB flash drives, external hard drives and SSDs.

Specifications

Appearance

Dimensions	67.6 mm x 45 mm x 15.2 mm (2.66" x 1.77" x 0.60")
Weight	26 g (0.91 oz)
Color	Black

Interface

USB Type	micro USB to USB Type A
Connection Interface	USB 3.1 Gen 1

Hardware

Card Reader Slot(s)	CFast
---------------------	-------

Operating Environment

Operating Temperature	0°C (32°F) ~ 70°C (158°F)
Operating Voltage	5V

Performance

Note	Speed may vary due to host hardware, software, usage, and storage capacity.
------	---

Warranty

Certificate	CE / FCC / BSMI / KC / RCM / EAC
Warranty	Two-year Limited Warranty

System Requirement

Operating System	Microsoft Windows 7 Microsoft Windows 8 Microsoft Windows 10 Mac OS X 10.2.8 or later Linux Kernel 2.6.30 or later
------------------	--

Compatibility

Memory Card Supported	CFast 2.0
-----------------------	-----------

Ordering Information

OMB	TS-RDF2
-----	---------

Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment.