

Body Cameras

POLICE

DrivePro[™] Body 30

Transcend's DrivePro Body 30 is a feature-packed body camera designed specifically for public safety professionals. With a twelve-hour battery life, IP67 rated environmental sealing, military-grade shock resistance, and a pre-event buffer, the DrivePro Body 30 is always ready for action. The Sony image sensor, high-quality lens, automatic infrared illumination, and six-axis image stabilization guarantee clear, high-definition evidence collection. Paired with Transcend's DrivePro Body App for iOS and Android smartphones, users can easily control the DrivePro Body 30 and manage videos and photos on the device.



Sony high-sensitivity image sensor

The DrivePro Body 30 features Sony sensor to capture high-resolution images with superb, rich color even in low light. Images are highly detailed with low noise and excellent balance between light and dark areas.



Infrared LEDs for night vision

The DrivePro Body 30 has four infrared LEDs that will automatically turn on in dim light to enhance night vision capabilities. This can drastically increase recording quality in pitch-black darkness.



Image stabilization technology

To minimize blurriness while moving and using the camera, the DrivePro Body 30 features a six-axis MEMS sensor that reduces the effect of motion on the camera.





Body Cameras DrivePro[™] Body 30

Features

- \cdot High sensitivity Sony image sensor
- · Infrared LEDs for night vision
- · Six-axis image stabilization technology
- Built-in 12-hour battery for long
 recording time
- Compliant with IP67 and U.S. military standards to be dust-proof, waterproof, and shock resistant

Transcend

DrivePro Body Toolbox

Transcend's DrivePro Body Toolbox is exclusively designed for the DrivePro Body series, featuring a user-friendly interface that allows users to securely manage recorded videos and snapshots on Windows PCs. In addition, users can adjust settings for both the toolbox and the DrivePro Body device, format the internal storage, and upgrade the body camera's firmware via the toolbox.

Specification

Specification	
Appearance	
Dimensions (Max.)	95.9 mm x 52.2 mm x 27.6 mm (3.78" x 2.06" x 1.09")
Weight (Max.)	130 g (4.59 oz)
Interface	
USB Type	3.5mm plug to USB Type A
Connection Interface	USB 2.0
Storage	
Capacity	64GB internal memory
Hardware	
Viewing angle	130° (diagonal)
Aperture	F/2.0
Power	
Battery Life (Fully Charged)	12 hour(s)
Power Supply (Max.)	Input: AC 100V-240V, 50-60Hz, 0.4A Output: DC 5V / 2A
Format	
Resolution	Full HD 1080P
Frame Rate	30 fps
Video Format	MOV (H.264)
Operating Environme	nt
Operating Temperature	-20°C (-4°F) ~ 65°C (149°F)
	-20°C (-4°F) ~ 65°C (149°F) -25°C (-13°F) ~ 70°C (158°F)

Warranty

Warranty	Two-year Limited Warranty
Certificate	CE/FCC/BSMI/NCC/MIC

Ordering Information

6	4GB	TS64GDPB30A
---	-----	-------------



Body Cameras Comparison













DrivePro[™] Body 60 Driv

DrivePro[™] Body 30 Drive

DrivePro™ Body 52

DrivePro™ Body 20

DrivePro[™] Body 10

Dimensions (Max.) x 24.9 mm (3.78" x 2.06" x 0.98") x 27.6 mm (3.78" x 2.06" x 1.09") x 17.4 mm (3.48" x 2.06" x 0.68") (3.4 Camera Dimensions (Max.) 61.3 mm x 22 mm x 22 mm (2.41" x 0.87" x 0.87") - 40 mm x 40 mm x 20.35 mm (1.57" x 1.57" x 0.80") Weight (Max.) 167 g (5.89 oz) 130 g (4.59 oz) 84 g (2.96 oz) 2 Camera Weight (Max.) - - 64 g (2.26 oz) 1 Interface USB Type 3.5mm plug to USB Type A 3.5mm plug to USB Type A . . . Capacity 64GB internal memory 64GB internal memory 32GB internal memory 32GB . . . Viewing angle 130° (diagonal) 130° (diagonal) 130° (diagonal) . . Aperture F/2.8 F/2.0 F/1.8 . . . Wi-Fi ✓ ✓ ✓ ✓ . . . Bluetooth ✓ ✓ ✓ ✓ . . . Wi-Fi ✓ ✓<	2.4 mm x 52.2 mm x 19.4 mm 48" x 2.06" x 0.76") - 88 g (3.10 oz) - 3.5mm plug to USB Type A Bi internal memory 160° (diagonal) F/2.8 - - -	88.4 mm x 52.2 mm x 19.6 mm (3.48" x 2.06" x 0.77" - 88 g (3.10 oz) -
Dimensions (Max.) x 24.9 mm (3.78" x 2.06" x 0.98") x 27.6 mm (3.78" x 2.06" x 1.09") x 17.4 mm (3.48" x 2.06" x 0.68") (3.4 Camera Dimensions (Max.) 61.3 mm x 22 mm x 22 mm (2.41" x 0.87" x 0.87") - 40 mm x 40 mm x 0.035 mm (1.57" x 1.57" x 0.80") Weight (Max.) 167 g (5.89 oz) 130 g (4.59 oz) 84 g (2.96 oz) 2 Camera Weight (Max.) - - 64 g (2.26 oz) 1 Interface USB Type 3.5mm plug to USB Type A 3.5mm plug to USB Type A . . . Capacity 64GB internal memory 64GB internal memory 32GB internal memory 32GB . . . Hardware Viewing angle 130° (diagonal) 130° (diagonal) 130° (diagonal) . . . Ni-Fi Bluetooth Vibration Alert <td>x 19.4 mm 48" x 2.06" x 0.76") - 88 g (3.10 oz) - 3.5mm plug to USB Type A 3.5mm plug to USB Type A 4 5B internal memory 160° (diagonal) F/2.8 - -</td> <td>× 19.6 mm (3.48" × 2.06" × 0.77" - 88 g (3.10 oz) - - - - - - - - - - - - - - - - - - -</td>	x 19.4 mm 48" x 2.06" x 0.76") - 88 g (3.10 oz) - 3.5mm plug to USB Type A 3.5mm plug to USB Type A 4 5B internal memory 160° (diagonal) F/2.8 - -	× 19.6 mm (3.48" × 2.06" × 0.77" - 88 g (3.10 oz) - - - - - - - - - - - - - - - - - - -
Camera Dimensions (Max.) x 22 mm (2.41" x 0.87" x 0.87") - x 20.35 mm (1.57" x 1.57" x 0.80") Weight (Max.) 167 g (5.89 oz) 130 g (4.59 oz) 84 g (2.96 oz) 2 Camera Weight (Max.) - - 64 g (2.26 oz) 2 Interface - - 64 g (2.26 oz) 2 Interface - - 64 g (2.26 oz) 2 Interface - - 64 g (2.26 oz) 2 USB Type 3.5mm plug to USB Type A USB Type A USB Type A 2 Connection Interface - - USB 2.0 2 Storage - - USB 2.0 2 Hardware - - - - Viewing angle 130° (diagonal) 130° (diagonal) 130° (diagonal) Aperture F/2.8 F/2.0 F/1.8 - Sony Image Sensor - - - - Wi-Fi - - - - Bluetooth -	- 3.5mm plug to USB Type A B internal memory 160° (diagonal) F/2.8 – –	- micro USB to USB Type A 32GB 130° (diagonal) F/2.8 ✓ ✓
Camera Weight (Max.) - - 64 g (2.26 oz) Interface - - 64 g (2.26 oz) USB Type 3.5mm plug to USB Type A Connection Interface USB Type A USB Type A USB Type A Capacity 64GB internal memory 64GB internal memory 32GB internal memory 32G Hardware - - Viewing angle 130° (diagonal) 130° (diagonal) 130° (diagonal) Aperture F/2.8 F/2.0 F/1.8 Sony Image Sensor - - - Wi-Fi - - - Bluetooth - - - - Wi-Fi - - - - Bluftering Mode - - - - Event Recording - - - - Loop Recording - - - -	- 3.5mm plug to USB Type A B internal memory 160° (diagonal) F/2.8 – –	- micro USB to USB Type A 32GB 130° (diagonal) F/2.8 ✓ ✓
Interface USB Type 3.5mm plug to USB Type A 3.5mm plug to USB Type A 3.5mm plug to USB Type A Connection Interface USB Z.0 Storage 64GB internal memory 64GB internal memory 32GB internal memory 32G Hardware 130° (diagonal) 130° (diagonal) Viewing angle 130° (diagonal) 130° (diagonal) Aperture F/2.8 F/2.0 Infrared LEDs - ✓ Wi-Fi ✓ ✓ Bluetooth ✓ ✓ Vibration Alert ✓ ✓ Buffering Mode ✓ ✓ ✓ ✓ ✓ Loop Recording ✓ ✓	USB Type A B internal memory 160° (diagonal) F/2.8 – –	USB Type A 32GB 130° (diagonal) F/2.8 ✓ ✓
USB Type3.5mm plug to USB Type A3.5mm plug to USB Type A3.5mm plug to USB Type AConnection InterfaceUSB Type AUSB Type AStorage-USB 2.0Capacity64GB internal memory 64GB internal memory 32GB internal memory 32GBHardware-Viewing angle130° (diagonal)130° (diagonal)ApertureF/2.8F/2.0F/1.8Sony Image Sensor✓✓✓Wi-Fi✓✓✓Microphone✓✓✓Vibration Alert✓✓✓Buffering Mode✓✓✓Loop Recording✓✓✓	USB Type A B internal memory 160° (diagonal) F/2.8 – –	USB Type A 32GB 130° (diagonal) F/2.8 ✓ ✓
USB Type A USB Type A USB Type A Connection Interface USB Type A Storage - Capacity 64GB internal memory 64GB internal memory 32GB internal memory 32G Hardware - Viewing angle 130° (diagonal) 130° (diagonal) Aperture F/2.8 F/2.0 F/1.8 Sony Image Sensor - - - Wi-Fi - - - Mirephone - - - Vibration Alert - - - Buffering Mode - - - Loop Recording - - -	USB Type A B internal memory 160° (diagonal) F/2.8 – –	USB Type A 32GB 130° (diagonal) F/2.8 ✓ ✓
Storage 64GB internal memory 64GB internal memory 32GB internal memory 32G Hardware - Viewing angle 130° (diagonal) 130° (diagonal) Aperture F/2.8 F/2.0 F/1.8 Sony Image Sensor - - - Wi-Fi - - - Bluetooth - - - - Nicrophone - - - - Vibration Alert - - - - Buffering Mode - - - - - Loop Recording - - - - - -	160° (diagonal) F/2.8 –	130° (diagonal) F/2.8 ✓ ✓
Capacity 64GB internal memory 64GB internal memory 32GB internal memory 32G Hardware Viewing angle 130° (diagonal) 130° (diagonal) 130° (diagonal) Aperture F/2.8 F/2.0 F/1.8 Sony Image Sensor ✓ ✓ ✓ Infrared LEDs - ✓ ✓ Wi-Fi ✓ ✓ ✓ Bluetooth ✓ ✓ ✓ Vibration Alert ✓ ✓ ✓ Buffering Mode ✓ ✓ ✓ Event Recording ✓ ✓ ✓ Inop Recording ✓ ✓ ✓	160° (diagonal) F/2.8 –	130° (diagonal) F/2.8 ✓ ✓
Hardware Viewing angle 130° (diagonal) 130° (diagonal) Aperture F/2.8 F/2.0 F/1.8 Sony Image Sensor ✓ ✓ ✓ Infrared LEDs - ✓ ✓ Wi-Fi ✓ ✓ ✓ Bluetooth ✓ ✓ ✓ Vibration Alert ✓ ✓ ✓ Buffering Mode ✓ ✓ ✓ Event Recording ✓ ✓ ✓ Ioop Recording ✓ ✓ ✓	160° (diagonal) F/2.8 –	130° (diagonal) F/2.8 ✓ ✓
Viewing angle130° (diagonal)130° (diagonal)130° (diagonal)ApertureF/2.8F/2.0F/1.8Sony Image Sensor✓✓✓Infrared LEDs-✓✓Wi-Fi✓✓✓Bluetooth✓✓✓Microphone✓✓✓Vibration Alert✓✓✓Buffering Mode✓✓✓Event Recording✓✓✓Ioop Recording✓✓✓	F/2.8 - -	F/2.8
ApertureF/2.8F/2.0F/1.8Sony Image Sensor✓✓✓Infrared LEDs-✓-Wi-Fi✓✓✓Bluetooth✓✓✓Microphone✓✓✓Vibration Alert✓✓-Buffering Mode✓✓-Event Recording-✓✓Loop Recording✓✓✓	F/2.8 - -	F/2.8
Sony Image SensorImage SensorImage SensorInfrared LEDsImage SensorImage SensorWi-FiImage SensorImage SensorBluetoothImage SensorImage SensorBluetoothImage SensorImage SensorMicrophoneImage SensorImage SensorVibration AlertImage SensorImage SensorBuffering ModeImage SensorImage SensorEvent RecordingImage SensorImage SensorLoop RecordingImage SensorImage Sensor<	-	✓ ✓
Infrared LEDs-Wi-Fi✓✓Bluetooth✓✓Microphone✓✓Vibration Alert✓✓Buffering Mode✓✓Event Recording-✓✓✓✓		\checkmark
Wi-Fi✓✓Bluetooth✓✓Microphone✓✓Vibration Alert✓✓Buffering Mode✓✓Event Recording–✓Loop Recording✓✓		
Bluetooth✓✓Microphone✓✓Vibration Alert✓✓Buffering Mode✓✓Event Recording–✓Loop Recording✓✓	\checkmark	-
Microphone ✓ ✓ Vibration Alert ✓ ✓ Buffering Mode ✓ ✓ Event Recording – ✓ Loop Recording ✓ ✓		
Vibration Alert Image: Constraint of the second s	-	-
Buffering Mode ✓ ✓ Event Recording – ✓ Loop Recording ✓ ✓	\checkmark	\checkmark
Event Recording - - Loop Recording ✓ ✓	-	-
Loop Recording	-	-
	\checkmark	\checkmark
	\checkmark	\checkmark
Power		
Battery Life (Fully Charged)10 hour(s)12 hour(s)3.5 hour(s)	3.5 hour(s)	5 hour(s)
Power Supply (Max.) Input: AC 100V-240V, 50-60Hz, 0.4A Output	t: DC 5V / 2A	
Format		
Resolution Full HD 1080P		
Frame Rate 30 fps		
Video Format MP4 (H.264) MOV (H.264) MOV (H.264)	MOV (H.264)	MP4 (H.264)
Operating Environment		
IP Rating IP67 IP67 IPX4	IPX4	IPX4
Warranty		
Warranty Two-year Limited Warranty		